



VALVE HEAD M4 TYPE H PTFE

ART. NO. 405541

GENERAL



The KEOFITT CLASSIC M4 Sampling Valve is the smallest KEOFITT sampling valve. Used in all industries for decades. More than 120 standard valve configurations. Unique serial no. for each valve*.



The sampling valve can be used for any process sampling for microbiological, chemical and/or physical analysis.



Cleaning/sterilizing: Between batches: Valve in open position: Cleanable by means of CIP using the detergent solution suitable for the actual process media. Between samples: Valve in its normal closed position: cleanable by CIP as "Between batches" or the valve may be sterilized by means of steam SIP or chemical SIP using a procedure appropriate to the actual circumstances. For further advice, please contact KEOFITT. Not recommended for autoclave due to plastic parts.



Designed for sampling of liquids with a viscosity of up to approx. 100 cP containing no particles larger than Ø1.5 mm. Sampling of more viscous liquids is possible, only will it take longer (depending on process pressure).

FEATURES



Installation: Threaded socket connection M16x1



Membrane: PTFE (#400055)



Operation: Turn knob - spring loaded (opens clockwise).

CERTIFICATION*

Valve head: EU EC 1935/2004 · EU EC 2023/2006 · DK No. 681 25/05/2020 · ATEX 2014/34/EU ·

PED 2014/68/EU · FDA CFR 21 §177.2600 · USP Class VI · KEOFITT DoC.

Membrane: EU EC 1935/2004 · EU EC 2023/2006 · DK No. 681 25/05/2020 · FDA CFR 21 §177.2600 ·

USP Class VI \cdot ADI Free \cdot KEOFITT DoC.

TECHNICAL DATA

Material (process contact)

Membrane: PTFE, white (#400055)

Material (without process contact)

Steel parts: AISI 303 (1.4305) / AISI 316L (1.4404)

Turn knob: PA6 (black) / PTFE

Pressure & Temperature

Pressure: 0 - 10 bar / 0 - 145 psiTemperature: $1 - 150^{\circ}\text{C} / 34 - 302^{\circ}\text{F}$

Air supply: -

Net weight

Kg/lbs: 0.099 kg / 0.217 lbs

SPARE PARTS

#774041PTFE Parts for M4 head 400041/42/43/47PTFE







