

GASKET 3" CLAMP EPDM

ART. NO. 900093

GENERAL



KEOFITT has the widest selection of spare parts and accessories to complete your sampling system



Compatible with all KEOFIT sampling valves with clamp connection

FEATURES



Connection: 3" clamp



CERTIFICATION*

· EU EC 1935/2004 · FDA CFR 21 §177.2600 · USP Class VI

TECHNICAL DATA

Material:	EPDM (E80008PF - black)
Temperature range (in dry atmospheric air) :	-40°C - +140°C / -40°F - +284°
Storage recommendation:	According to ISO 2230
Specification:	ASTM D2000 M7CA 810 A25 B35 F1

Physical properties

Hardness, Shore A (pts):	81,00
Tensile strength (MPa):	14,96
Ultimate elongation (%):	160,00
Modulus at 100% (MPa):	7,34

Heat resistance, 70h at 125°C:

Change in hardness (pts):	3,00
Change in tensile strength (%):	3,00
Change in ultimate elongation (%):	-5,00

Compression set, method B:

22h at 125°C (%):	10
-------------------	----

Compression set, method B - 3 tests done:

22h at 150°C (%):	19,8
22h at 150°C (%):	23,3
22h at 150°C (%):	21,36

Low temperature resistance, method A:

3 min. at -40°C (%):	Non brittle
----------------------	-------------

Net weight (kg/lbs):	0,011 kg /0,024 lbs
----------------------	---------------------

